
PRODUCT INFORMATION



Applied Australia Pty Ltd (ABN 96 082 810 973) 92 FAIRBANK ROAD CLAYTON SOUTH VICTORIA 3169

Telephone (03) 8542 5111 Facsimile (03) 8542 5188

The Applied Group of Companies has Offices in: Australia, New Zealand, Asia & Europe.

APPLIED 2539

FOAMING ACID CLEANER

PRODUCT DESCRIPTION AND USE:

Applied 2-539 is a foaming acid cleaner specifically designed for removing brake dust build-up and other soils from railroad stock.

BENEFITS:

- Foams onto surface - ensuring maximum contact and minimum waste
- Effectively removes heavy build up of soils and brake dust
- Dissolves readily in water
- Safe on aluminium, steel, glass and good quality paints if used as recommended
- Contains no phosphates, silicates, or heavy metal salts.
- Surfactants are biodegradable.

PRODUCT CHARACTERISTICS:

- Clear, blue acidic liquid with no flash point
- Soluble in water to produce foaming solutions.

DIRECTIONS FOR USE:

Dilute cleaner with up to 60 parts water for routine cleaning. Apply through either high volume or low volume foamer. Allow to dwell for about two minutes. Rinse with high pressure water (2500 Kpa or more) or brush while water rinsing.

For cleaning heavily soiled areas, a concentration of 1 part cleanser with only 10 to 20 parts water may be required.

HANDLING PRECAUTIONS:

Avoid contact with eyes and skin. Can cause irritation. Avoid breathing spray mist. Use face shield or goggles, rubber gloves and other protective clothing as required. Use with adequate ventilation. Do not take internally. In case of accidental contact, flood with water. If eye irritation persists, seek medical attention.

For further information, please consult Material Safety Data Sheet.

For further information, please consult the Materials Safety Data Sheet.