

Rapsody I

Cleaning and Slip Agent

APPLIED A3982

Description:	Rapsody I is based on an organic ester designed to be an environmentally acceptable, non-hazardous replacement of diesel in cleaning and slip applications.
Intended Use:	<p>Rapsody I is an ideal cleaning and slip product for the asphalt and bitumen industry, capable of removing heavy grease and open gear compounds from metal surfaces.</p> <p>Excellent results are obtained when using Rapsody I for machinery wash downs, without affecting machinery surfaces.</p> <p>Rapsody I can create a non-stick barrier on truck beds, paving equipment and tool surfaces and is harmless to most paint and metal surfaces.</p> <p>Rapsody I is used to lubricate drag chains and slats, which cleans as it lubricates.</p>
Product features:	<p>Rapsody I works well as a cleaner on paving machines, trucks, concrete and hand tools. It can be used as a slipping agent in paving machines and trucks.</p> <p>Rapsody I as a truck slip is shown to work well with both hot and cold mixes. It has performed well with multiple truck tips even with long hauls or delays before tips. Rapsody I is an excellent water-based open gear grease remover.</p> <p>As a slat lube, it will reduce the wear on components and lead to savings on power required to run the system.</p>

Typical Physical Properties:

Technical data should be considered representative or typical only and should not be used for specification purposes.

Appearance:	Clear straw coloured liquid
Specific Gravity:	0.99
pH: (Neat):	7.4
Flash Point:	Non-flammable
Solubility:	Water soluble

Directions for Use:

SLIP & CLEANING AGENT

For the general use of Rapsody I as a cleaning and slipping agent for paving machines and hand tools, a dilution of 1 part Rapsody I to 1 - 2 parts water is recommended. This should be applied using a suitable spray applicator to avoid wastage.

As a truck slip, a dilution of 1 part Rapsody I to 1 - 3 parts water is recommended.

GREASE REMOVAL

For removal of open gear and other heavy greases, use neat, or for light contamination, dilute Rapsody I 1 part to 4 parts water.

IMPORTANT NOTE:

Rapsody is compatible with most materials of construction.

May soften paint or mark some grades of aluminium if allowed to remain in contact with the concentrated product for extended periods.

Storage:

Avoid temperature extremes.

Precautions:

Please refer to appropriate safety data sheet (SDS) prior to using this product.

For technical assistance, please call 1800-063-511

FOR INDUSTRIAL USE ONLY

Warranty:

Applied will replace any material found to be defective. Because the storage, handling and application of this material is beyond our control, we can accept no liability for the results obtained.

Disclaimer:

All information on this data sheet is based on laboratory testing and is not intended for design purposes. ITW Polymers & Fluids and Applied makes no representations or warranties of any kind concerning this data.

Order Information:

A3982-15	Applied Rapsody 15 L
A3982-200	Applied Rapsody 200 L
A3982-1000	Applied Rapsody 1000 L (IBC)