

Appсорb

Multi-Purpose liquid and oil absorber

APPLIED A3663

Description: **Applied Appсорb (A3663)** is calcined (super-heated) Diatomaceous Earth, a sedimentary rock made up primarily of amorphous silica.

Appсорb is an extremely effective absorbent that is used in a wide range of industries, tanneries, canning plants, packing plants, textile mills, garages, workshops, petrol stations, etc.

Appсорb can be used on many types of lubricants, light oils, cutting oils, soluble oil emulsions, water, grease, acids, solvents, syrups and other liquid and semi-liquid materials.

Intended Use: **Appсорb** is especially used for:

- Reclamation and preservation of floors.
- Absorptive banking around machinery and walls.
- Reclamation of soil-soaked gloves, clothing, belting, etc.
- Annealing of high carbon steel, cooling of forgings.
- Elimination of bleeding of pitch, tar, creosote, etc., from treated wood.
- Absorption of spilled cyanide in case hardening processes, or optical rouge in polishing rooms.
- Use as a sweeping compound after saturation with oil.
- Protection of rubber hoses, tyres, from oil rot.
- Absorption of oil and grease drippings.

Product features: **A versatile, granulated absorbent.**

Easy and convenient to use.

Reduces maintenance of floors.

Improves working conditions.

Lowers risk of accident.

Will not support combustion.

Absorbs up to 100% of its own weight in liquid.

Will not break down or "mud" - even after prolonged use.

Non-crystalline silica

Typical Physical Properties: *Technical data should be considered representative or typical only and should not be used for specification purposes.*

Appearance: **White to light grey fine granules.**

Directions for Use:

- Using **Appсорb** is simplicity itself.
- Just sprinkle **Appсорb** on the contamination, allow to stand for a short time and sweep up.

Storage: Store at 0°C - 59°C.

Precautions: Please refer to appropriate safety data sheet (SDS) prior to using this product.
For technical assistance, please call 1800-063-511
FOR INDUSTRIAL USE ONLY

Warranty: Applied will replace any material found to be defective. Because the storage, handling and application of this material is beyond our control, we can accept no liability for the results obtained.

Disclaimer: All information on this data sheet is based on laboratory testing and is not intended for design purposes. ITW Polymers & Fluids and Applied makes no representations or warranties of any kind concerning this data.

Order Information: A3663-40 Applied Appсорb 20kg / 40 L