

Parts Washer Degreaser

Rapid Break Solvent Degreaser

APPLIED A8413

Description:	<p>Parts Washer Degreaser (A8413) is a neutral, emulsifiable solvent which is used as supplied for cleaning engines, chassis, plant, machinery and equipment. It will not attack sound paint work.</p> <p>Parts Washer Degreaser is a first class soak tank cleaner used at room temperature in a mild steel tank.</p> <p>Parts Washer Degreaser is fit for Purpose as a General Cleaner Type C per the requirements for the use of chemicals in the export registered meat and meat product establishments, as published in AQIS Meat Export Gazette Notice No. 2011/05</p>												
Intended Use:	<p>Parts Washer Degreaser is used as a parts washer degreaser in the automotive industry and is suitable for manual use and recirculating parts washing machines.</p>												
Product features:	<p>Quickly penetrates and removes oil, grease, dirt and asphalt compounds Formulated for use with oil interceptors No mixing required - ready to use No heating required, use at room temperature Simple to apply - low pressure spray or immersion Safe on all metals</p>												
Typical Physical Properties:	<p><i>Technical data should be considered representative or typical only and should not be used for specification purposes.</i></p> <table border="0"> <tr> <td>Appearance:</td> <td>Clear amber liquid.</td> </tr> <tr> <td>Odour:</td> <td>Strong kerosene like odour</td> </tr> <tr> <td>Specific Gravity (g.cm⁻¹):</td> <td>0.82 @ 20°C</td> </tr> <tr> <td>Flash Point:</td> <td>84°C (open cup)</td> </tr> <tr> <td>Auto ignition temperature:</td> <td>340°C</td> </tr> <tr> <td>Flammability:</td> <td>Combustible. Classified as a C1 Combustible Liquid according to AS1940-2004</td> </tr> </table>	Appearance:	Clear amber liquid.	Odour:	Strong kerosene like odour	Specific Gravity (g.cm⁻¹):	0.82 @ 20°C	Flash Point:	84°C (open cup)	Auto ignition temperature:	340°C	Flammability:	Combustible. Classified as a C1 Combustible Liquid according to AS1940-2004
Appearance:	Clear amber liquid.												
Odour:	Strong kerosene like odour												
Specific Gravity (g.cm⁻¹):	0.82 @ 20°C												
Flash Point:	84°C (open cup)												
Auto ignition temperature:	340°C												
Flammability:	Combustible. Classified as a C1 Combustible Liquid according to AS1940-2004												
Directions for Use:	<p>Brush or swab Parts Washer Degreaser onto components to be degreased, rinse afterwards if necessary.</p> <p>Soak Tank:</p> <ol style="list-style-type: none"> 1. Immerse components for 15-20 minutes. 2. Remove components and allow to drain. 3. Pressure rinse with clean water. <p>Spray:</p> <ol style="list-style-type: none"> 1. Spray Parts Wash Degreaser onto the surface to be cleaned. 2. Allow to soak for 5-20 minutes depending on the type and amount of soil. 3. Pressure rinse with clean water. <p>Food Plants</p> <p>In cleaning and degreasing in food plants, Parts Washer Degreaser is limited to use in non-processing areas where there is NO possibility of solvent vapours entering a processing area. Food processing equipment treated with Parts Washer Degreaser must be washed with a food-contact approved detergent and thoroughly rinsed with potable (drinking) water before return to a food processing area.</p>												
Storage:	Store at 1°C - 40°C.												
Precautions:	<p>Please refer to appropriate safety data sheet (SDS) prior to using this product. For technical assistance, please call 1800-063-511 FOR INDUSTRIAL USE ONLY</p>												
Warranty:	Applied will replace any material found to be defective. Because the storage, handling and application of this material is beyond our control, we can accept no liability for the results obtained.												
Disclaimer:	All information on this data sheet is based on laboratory testing and is not intended for design purposes. ITW Polymers & Fluids and Applied makes no representations or warranties of any kind concerning this data.												
Order Information:	<table border="0"> <tr> <td>A8413-20</td> <td>Applied Parts Wash Degreaser 20 L</td> </tr> <tr> <td>A8413-205</td> <td>Applied Parts Wash Degreaser 205 L</td> </tr> <tr> <td>A8413-1000</td> <td>Applied Parts Wash Degreaser 1000 L (IBC)</td> </tr> </table>	A8413-20	Applied Parts Wash Degreaser 20 L	A8413-205	Applied Parts Wash Degreaser 205 L	A8413-1000	Applied Parts Wash Degreaser 1000 L (IBC)						
A8413-20	Applied Parts Wash Degreaser 20 L												
A8413-205	Applied Parts Wash Degreaser 205 L												
A8413-1000	Applied Parts Wash Degreaser 1000 L (IBC)												