

Rimtreat X[®]

Tyre & Rim Sealant, Corrosion Inhibitor

APPLIED A3421

Description:

RIMTREAT X[®] is an advanced formulation designed to inhibit corrosion on rims.

Intended Use:

RIMTREAT X[®] can be used in all applications where a ready to use corrosion inhibitor is required however, it is especially designed for use in large tubeless tyres found in the mining industry.

Product features:

Contains a ferrous metal and brass brightening agent ... rims are clean, bright and take less time to clean.

Contains advanced corrosion inhibitors ... Offers superior protection and prevention of rim corrosion.

Classified as non-hazardous ... safe to handle and use.

Typical Physical Properties:

Technical data should be considered representative or typical only and should not be used for specification purposes.

Appearance: Low viscosity dark-green liquid

Odour: Extremely low odour

pH (Concentrate): 7.3 – 7.7

Directions for Use:

- RIMTREAT X[®] should be added to the wheel as received.
- Dosing will be dependent on wheel size.

DISPENSING: Contact your Applied Representative for information on the various air operated dispenser systems available for dispensing of RIMTREAT X[®].

APPLICATION RATES FOR TYRE SIZE

TYRE SIZE	LITRES
1200 x 24/25; 1300 x 24/25; 1400 x 24/25	5.0
15.5 x 25; 1600 x 24/25; 17.5 x 25; 1800 x 24/25	5.5
20.5 x 25; 23.5 x 25; 2100 x 24/25	9.0
26.5 x 25; 29.5 x 25; 2400 x 25; 1800 x 33	12.0
2100 x 35; 2400 x 35; 2400 x 49; 26.5 x 29	14.0
33.5x33; 33.25 x 35; 2700 x 49; 2700 x 33; 29.5 x 35; 90 x 33.7	20.0
37.25 x 33; 37.5 x 33; 27.5 x 39; 65/35 x 33; 37.2 x 35; 37.5 x 3300 x 39; 41.25/70 x 39; 65/45 x 39; 40/65 x 39; 3000 x 51; 3300 x 51	30.0
65/45 x 45; 45/65 x 45	30
3600 x 51; 50/65 x 51; 667.5/60 x 51	38
3700 x 57; 4000 x 57	40
44/80 x 57	46
50/80 x 57; 53/80 x 57	54
60/80 x 57, 53/80 x 63; 70/70 x 57, 55/80 x 63, 59/80 x 63	62

IMPORTANT:

- To ensure total tyre and wheel protection, correct quantities of RIMTREAT X[®] are required to provide adequate cooling, rust and oxidation control.
- Severely damaged inner rims, extreme operating conditions, or badly rusted rims may require an increase of up to 50% above recommendations.
- Magnesium and aluminium wheels - use the quantity recommended to provide adequate sealing of wheel porosity.

Storage:

Avoid temperature extremes.

Precautions:	Please refer to appropriate safety data sheet (SDS) prior to using this product. For technical assistance, please call 1800-063-511 FOR INDUSTRIAL USE ONLY
Warranty:	Applied will replace any material found to be defective. Because the storage, handling and application of this material is beyond our control, we can accept no liability for the results obtained.
Disclaimer:	All information on this data sheet is based on laboratory testing and is not intended for design purposes. ITW Polymers & Fluids and Applied makes no representations or warranties of any kind concerning this data.
Order Information:	A3421-1000 Applied Rimtreat X [®] 1000 L (IBC) RIMTREAT X [®] is a trademark of Illinois Tool Works Inc.