

# TECHNICAL DATA

## GALMET THINNERS

### GALMET ENAMEL SPRAY THINNER 300C

#### Fast enamel spraying thinner

##### Description

**Galmet Enamel Spraying Thinner 300C** is a fast evaporating thinner formulated for spraying Galmet enamel coating products. It is also suitable for cleaning and degreasing metal surfaces prior to painting.

##### Areas of Application

- Galmet Rustpaint
- Galmet Spraypaint
- Galmet Hammered Metal Finish
- Galmet Keytite Steel Primer
- Galmet Industrial Primers
- Galmet Blue Plus Paint
- Galmet Pot Belly Paint

### GALMET INDUSTRIAL THINNER 400D

#### Aromatic thinner

##### Description

**Galmet Industrial Thinner 400D** is a slow evaporating thinner with strong solvent action for spraying and clean up of **Galmet Cold Galvanizing** chlorinated rubber products

##### Areas of Application

- Galmet Cold Galvanizing Standard
- Galmet Duragal

### GALMET ETCH THINNER 500E

#### Etch thinner

##### Description

**Galmet Etch Thinner 500E** is a fast evaporating thinner with strong solvent action for spraying and clean up of Galmet products that cure by solvent evaporation.

##### Areas of Application

- Galmet Keytite Etch Primer

---

The information enclosed in this Technical Bulletin is as up to date and correct as possible as at the time of issue. The data provided in this Technical Bulletin should be used as a guide only, as the performance of the product will vary depending on differing operating conditions and application methods.

The sale of any product described in this Technical Bulletin will be in accordance with ITW Polymers & Fluids Pty Ltd Conditions of Sale, a copy of which is available on request. To the extent permitted by law, ITW Polymers & Fluids Pty Ltd excludes all other warranties in relation to this product.

**Directions for Use**

- Refer to the Technical Data Sheets for individual Galmet products for recommendations on correct thinner to use and proportions.

**Technical Data**

	<b>Thinner 300C</b>	<b>Thinner 400D</b>	<b>Thinner 500E</b>
<i>Appearance:</i>	Clear liquid	Clear liquid	Clear liquid
<i>Flash Point:</i>	-1° C	38 - 50° C	-4° C

**Health & Safety Information**

- Avoid contact with skin and eyes; avoid breathing vapour and spray mist.
- If poisoning occurs contact the Poisons Information Centre.
- If swallowed, do not induce vomiting; drink a glass of water.
- If in eyes rinse with water for 15 minutes and see a doctor.
- For more information consult the Material Safety Data Sheet for this product.

**Galmet Enamel Spray Thinner 300C**

- UN1263 – Paint
- Class 3 – Flammable Liquid
- Packaging Group III

**Galmet Industrial Thinner 400D**

- UN1263 – Paint
- Class 3 – Flammable Liquid
- Packaging Group III

**Galmet Etch Thinner 500E**

- UN1263 – Paint
- Class 3 – Flammable Liquid
- Packaging Group III

**AUSTRALIA**

ITW Polymers & Fluids  
100 Hassall Street  
Wetherill Park NSW 2164  
Phone (02) 9757 8800 Fax (02) 9757 3855

**NEW ZEALAND**

ITW Polymers & Fluids  
Unit 2/38 Trugood Drive  
East Tamaki 2013, Auckland  
Phone (09) 272 1945 Fax (09) 273 6489