

TECHNICAL DATA

MOLYBOND HE50 Spray

Wet film assembly spray containing molybdenum disulphide

Description

Molybond HE50 wet film assembly spray is a 50% molybdenum disulphide in oil dispersion. HE50 Spray eliminates scuffing and bearing "pick up" during the initial operating period or assembly of machined components.

Areas of application

- Engines
- Gearboxes
- Cylinders
- Bearings
- Press fitted components

Features

- Easily applied
- Eliminates scuffing
- Reduces plain bearing "pick up" during initial operating period

Directions for use

Shake well before use. Hold can upright and spray from a distance of 15 to 30 cm. Use only as directed.

Technical data

AppearanceBlack Oil
Lubricating Solids50% Molybdenum Disulphide
Base OilMineral Oil

The information enclosed in this Technical Bulletin is as up to date and correct as possible as at the time of issue. The data provided in this Technical Bulletin should be used as a guide only, as the performance of the product will vary depending on differing operating conditions and application methods.

The sale of any product described in this Technical Bulletin will be in accordance with ITW Polymers & Fluids Pty Ltd Conditions of Sale, a copy of which is available on request. To the extent permitted by law, ITW Polymers & Fluids Pty Ltd excludes all other warranties in relation to this product.

Health & safety information

The product contains flammable gas. Keep away from sources of ignition. Do not breathe in spray. Use only in well ventilated areas. A Material Safety Datasheet is available from the Rocol Customer Services Department upon request. KEEP OUT OF REACH OF CHILDREN. This product is non-hazardous.

Australia

ITW Polymers & Fluids Pty Ltd
100 Hassall Street, Wetherill Park, NSW, 2164
Phone: (02) 9757 8800
Fax: (02) 9757 3855

New Zealand

ITW Polymers & Fluids
18-26 Amelia Earhart Ave, Airport Oaks, Mangere
Phone: 09 256 2122
Fax: 09 256 2124