

# TECHNICAL DATA

## MOLYGEAR 320

### G1700

#### Description

**Molygear 320** is an ISO VG 320 grade general purpose, long life industrial gear oil containing molybdenum disulphide.

**Molygear 320** meets the requirements of the following: U.S. Steel 224, Cincinnati Milacron, AGMA 250.4, AGMA 251.02, DIN51517 Part 3.

#### Areas of application

- Industrial gear boxes
- Worm drive gears
- Conveyor drive gear boxes

#### Features

- Increases component life
- Reduces operating temperatures
- Increases oil drain intervals – oil change intervals up to 20,000 hours
- General purpose – reduces lubricant stockholdings
- Meets Australian Mining and Heavy Industrial Environment requirements

---

The information contained in this Technical Bulletin is as up to date and correct as possible as at the time of issue. The data provided should be used as a guide only as the performance of the product will vary depending on differing operating conditions and application methods.

The sale of any product described in this Technical Bulletin will be in accordance with ITW Polymers & Fluids Conditions Of Sale, a copy of which is available on request. To the extent permitted by law, ITW Polymers & Fluids excludes all other warranties in relation to this product.

## Technical data

	Test Method
Appearance .....	Black liquid
ISO Viscosity Grade.....	320
Viscosity Index .....	96
Lubricating Solids.....	Molybdenum Disulphide
Viscosity at 40°C (cst) .....	3 20
Viscosity at 100°C (cst) .....	24
'4 Ball'	
Weld Load (kg).....	620
Wear Scar (mm).....	0.3
Timken 'OK' Load (kg).....	36
Pour Point °C .....	-15
Flash Point COC °C .....	202
	ASTM D2270
	ASTM D445
	ASTM D445
	ASTM D2596 (IP239)
	ASTM D4172
	ASTM D2782
	ASTM D-92

## Directions for use

The product is applied in the same way as conventional gear oils.

## Storage and Shelf Life

Store in dry conditions between 0°C and 50°C, away from sources of heat and naked flames. When stored in original sealed containers, the minimum shelf life is four (4) years.

## Packaging

**Molygear 320** is available in 20 Lt and 205 Lt drums.

## Ordering Information:

20 Lt drum	#RC204389
205 Lt drum	#RC204396

## Health & Safety Information

The product is non-hazardous. A Material Safety Data Sheet is available from the ITW Polymers & Fluids Technical Department upon request or available on our website [www.molybond.com.au](http://www.molybond.com.au).

---

### AUSTRALIA

ITW Polymers & Fluids  
100 Hassall Street  
Wetherill Park NSW 2164  
Phone (02) 9757 8800 Fax (02) 9757 3855

### NEW ZEALAND

ITW Polymers & Fluids  
18-26 Amelia Earhart Avenue  
Airport Oaks, Mangere, Auckland  
Phone (09) 256 2122 Fax (09) 256 2124