

## FLUID WIRE ROPE GREASE

### *RD205*

#### Description

**Fluid Wire Rope Grease** is a fluid grease containing petroleum solvent which slowly evaporates to form a film containing a powerful dewatering agent that may be applied to wet ropes.

**Fluid Wire Rope Grease** penetrates the strands to the core of the rope providing complete rope lubrication. Not recommended where friction drum brakes are used such as in elevators.

#### Areas of application

- Wire ropes
- Dockyard cranes
- Mobile Cranes
- Chair lifts
- Flying foxes
- Slipways

#### Features

- Rapidly penetrates wire ropes
- Provides excellent anti-wear properties
- Repels water
- Protects against corrosion
- Carries high loads
- NZFSA Approved C12 (All animal product except dairy)
- AgriQuality Approved

---

The information contained in this Technical Bulletin is as up to date and correct as possible as at the time of issue. The data provided should be used as a guide only as the performance of the product will vary depending on differing operating conditions and application methods.

The sale of any product described in this Technical Bulletin will be in accordance with ITW Polymers & Fluids Conditions Of Sale, a copy of which is available on request. To the extent permitted by law, ITW Polymers & Fluids excludes all other warranties in relation to this product.

## Technical data

Appearance .....	Black Liquid Grease
Thickener.....	Organic Modified Clay
Oil.....	Solvent Refined Mineral
Temperature Range	
Operating .....	-20°C to 100°C
Min. for Application .....	-10°C
Pour Point Base Oil.....	-10°C
Viscosity at 60°C (cst).....	160

## Directions for use

The product may be applied through either air operated or airless spray equipment. Alternately it may be applied by brush or swab.

Where problems have been met with over application of **Rocol® I Wire Rope Grease**, and **Rocol® Fluid Wire Rope Grease** may be applied by brush and will be found easier to "brush out". Care needs to be taken not to over apply otherwise dripping will occur before the solvent has evaporated.

## Storage and Shelf Life

Store in dry conditions between 0°C and 50°C, away from sources of heat and naked flames. When stored in original sealed containers, the minimum shelf life is four (4) years.

## Packaging

**Fluid Wire Rope Grease** is available in a 20 Lt Drum.

## Ordering Information:

20 Lt Drum                      RY453321

## Safety Precautions

Follow normal coating precautions. Contents are flammable. Keep away from fire or naked flame. Keep contents away from children. If swallowed call a Doctor or Poisons Information Centre. When mixing or using, avoid skin contact or breathing of vapours. If splashed on skin, wash with warm soapy water. During application, wear protective clothing and where necessary, goggles and mask or respirator. Provide adequate fresh air ventilation.

**TDG Code:** Not classified

## Health & Safety Information

The product is hazardous. A Material Safety Data Sheet is available from the ITW Polymers & Fluids Technical Department upon request or available on our website [www.rocol.com.au](http://www.rocol.com.au).

---

### AUSTRALIA

ITW Polymers & Fluids  
100 Hassall Street  
Wetherill Park NSW 2164  
Phone (02) 9757 8800 Fax (02) 9757 3855

### NEW ZEALAND

ITW Polymers & Fluids  
Unit 2 / 38 Trugood Drive  
East Tamaki 2013, Auckland  
Phone (09) 272 1945 Fax (09) 273 6489