



ROCOL Copper Anti-Seize Spray

Anti-seize spray

Description

Rocol Copper Anti-Seize Spray is designed to prevent galling, pick-up and fretting on all static joints and threaded connections. The thin film protects against wet dirty conditions and chemical attack which are the main causes of corrosive seizure. Copper Anti-Seize contains lubricating solids to eliminate seizure during assembly or dismantling after long periods under heavy loads.

Areas of application

- Industrial fasteners
- Furnaces and kilns
- Drying ovens
- Moulding die assembly
- Marine equipment
- High load couplings

Features

- Provides long-term protection against seizure in extreme conditions
- Provides anti-seize properties up to 1100°C
- Excellent water resistance
- Easy to apply to difficult profiles or restricted spaces
- Contains no leaded additives
- Easily applied during assembly
- NZFSA Approved C12 (All animal product except dairy)

Directions for use

Shake can well before use. Hold upright and spray a thin even coating over the threads from a distance of 15 to 30cm. Test compatibility with painted and coated surfaces, plastics and rubbers, prior to application. Use only as directed. After use, invert can and spray to clear nozzle.

Technical data

Appearance	Copper Coloured Grease
Lubricating Solids	Copper
Carrier	Bentonite Thickened Mineral Oil
Temperature Range.....	up to 1100°C
Propellant.....	Hydrocarbon

Health & safety information

The product contains flammable gas. Keep away from sources of ignition. Do not breathe in spray. Use only in well ventilated areas. A Material Safety Datasheet is available from the Rocol Customer Services Department upon request. KEEP OUT OF REACH OF CHILDREN. This product is non-hazardous.

The information enclosed in this Technical Bulletin is as up to date and correct as possible as at the time of issue. The data provided in this Technical Bulletin should be used as a guide only, as the performance of the product will vary depending on differing operating conditions and application methods.

The sale of any product described in this Technical Bulletin will be in accordance with ITW Polymers & Fluids Pty Ltd Conditions of Sale, a copy of which is available on request. To the extent permitted by law, ITW Polymers & Fluids Pty Ltd excludes all other warranties in relation to this product.

